

# NO TOOLS JUST PULL STRAIGHT FROM THE BARREL

# NO EXTRA TOOLS NEEDED Remove the Cyclone Barrel Pack lid,

Remove the Cyclone Barrel Pack lid, detach wire from its secured position and attach wire to your pull rope.

### **FULLY CUSTOM BARREL PACK**

Available in 14 AWG through 10 AWG up to 7 conductors. Multiple conductors eliminate the need for numerous reels.

### **PORTABLE & EASY TO SET UP**

Handle the Cyclone Barrel Pack with any industrial dolly or cart; no need to buy special equipment or tools.

AVAILABLE IN 55 AND 75 GALLON DRUMS



### **CYCLONE DESIGN**

Center cone for tool-free pulling.

TEAR HERE

Save 80% Total time

SAVE 84% ON PULL TIME SAVE 50% ON CLEAN-UP TIME

**SAVE 75% ON SETUP TIME** 

## ENVIRONMENTAL RESPONSIBILITY

Lower the amount of wire scrap produced, while decreasing the waste produced by packaging.

**EFFORTLESS PULLING** 

No tangles, no tools, just pull!



**ENCORE WIRE®** 

1.800.962.9473 | encorewire.com













# ADVANTAGES OF THE CYCLONE BARREL PACK

- Available in THHN/THWN-2 Stranded only
- 120V/208Y and 277V/480Y color-coding
- Portable and easy to set up
- Barrel serves as an instant payoff system
- Eliminates the need for multiple reels
- Lowers the amount of wire scrap produced
- Less waste created by barrel pack vs. reel
- Money and time savings on job site or OEM shop
- Less space on a truck than traditional reels
- Longer continual runs
- Available in 14 AWG through 10 AWG up to 7 conductors
- Easily customized to any specific job
- Available in 55 and 75 gallon drums

### THHN/THWN-2 COPPER FOOTAGE CHART STRANDED

Wire Type	Length (ft)	Total Footage (ft)
14/2 STR THHN/THWN-2	10,500'	21,000'
14/3 STR THHN/THWN-2	9,000'	27,000'
14/4 STR THHN/THWN-2	7,000'	28,000'
14/5 STR THHN/THWN-2	7,000'	35,000'
14/6 STR THHN/THWN-2	5,000'	30,000'
14/7 STR THHN/THWN-2	5,000'	35,000'
12/2 STR THHN/THWN-2	8,000'	16,000'
12/3 STR THHN/THWN-2	6,750'	20,250'
12/4 STR THHN/THWN-2	5,000'	20,000'
12/5 STR THHN/THWN-2	5,000'	25,000'
12/6 STR THHN/THWN-2	3,000'	18,000'
12/7 STR THHN/THWN-2	3,000'	21,000'
10/2 STR THHN/THWN-2	5,000'	10,000'
10/3 STR THHN/THWN-2	4,250'	12,750'
10/4 STR THHN/THWN-2	3,000'	12,000'
10/5 STR THHN/THWN-2	3,000'	15,000'
10/6 STR THHN/THWN-2	2,500'	15,000'
10/7 STR THHN/THWN-2	2,500'	17,500'

